

ANNN YANG

CLUTCH LATHE DY-560M~760M

BED WIDTH 410MM



DY 560x2000M

MODEL		DY-560M	DY-660M	DY-760M
Swing	Distance between centers 1000/1500/2000/2500/3000/4000/5000/6000mm			
	Height of center (over bed)	280mm	330mm	380mm
	Swing over bed	560mm	660mm	760mm
	Swing over cross slide	310mm	410mm	510mm
	Over gap swing	800mm	900mm	1000mm
Bed	Bed width	410mm		
Headstock	Spindle nose	D1-8 / D1-11 (opt)		
	Spindle bore	104mm / 130mm(opt)		
	Spindle speed (rpm)	25~1250rpm		
	Number of spindle speed	12 Change		
Feeds- Thread	Leadscrew	Ø45 mm, 2T.P.I. or 6 pitch		
	Number of feed changes	36		
	Longitudinal feed range	0.05~0.70 mm/rev		
	Cross feed range	0.025~0.35mm/rev		
	Inch threads	2~28 T.P.I.		
	Metric threads	P0.8~14mm		
	D.P. No. / range	D.P 4~56		
	Module pitches No. / range	MOD 0.5~7		
Tool slide	Cross slide travel	380 mm		
	Compound rest travel	255 mm		
Tailstock	Quill travel	180mm		
	Quill diameter	75mm		
	Taper of center	MT#5		
Motor	Main motor	15HP / 20HP (Opt.)		
	Rapid feed motor	1/4HP		
	Coolant pump	1/8HP		
Length	2800/3300/3800/4300/4800/5800/6800/7800mm			
Width	1400			
Height	1530	1630	1730	
N.W. (kg) (approx.)	2400/2700/3000/3300/3700/4500/5200/6000kg			
Workpiece Weight capacity		Chuck only	Chuck + Tailstock	Chuck + 1 Steady rest + Tailstock
Chuck + 2 Steady rest + Tailstock				
Spindle bore 104mm		500kg	1200kg	2000kg
Spindle bore 130mm		600kg	1300kg	2100kg

* ABOVE SPECIFICATIONS ARE FOR YOUR REFERENCE AND SUBJECT TO CHANGE WITHOUT NOTICE, FOR SPECIAL REQUIREMENTS PLEASE CONTACT US.

www.annnyang.com

DY-680~980VS

DY-860~1100VS

DY-1100~1500VS

DY-460~510M

DY-560~760M