


ANNN YANG

CONVENTIONAL LATHE DY-680G~980G BED WIDTH 458MM



DY 680GX3000

MODEL		DY-680G	DY-780G	DY-880G	DY-980G
Swing	Distance Between Centers	1100/1600/2000/2500/3000/3500/4000/5000/6000/7000/8000/9000/10000mm			
	Swing over bed	680mm	780mm	880mm	980mm
	Swing over cross slide	440mm	540mm	640mm	740mm
	Over gap swing (mm)	970X482	1070X482	1170X482	1270X482
Bed	Height of center (over bed)	340mm	390mm	440mm	490mm
	Bed width	458mm			
Headstock	Spindle nose	A2-11 or D1-11		A2-11 or D1-11	
	Spindle bore	105mm (STA.)		150mm (OPT.)	
	Spindle speed (rpm)	15,24,32,45,60,95,130,180,340,530,720,1000		14,22,30,40,50,80,110,150,280,430,600,800	
	Number of spindle speed	12 steps			
Feeds- Thread	Leadscrew	Ø45 mm, 2T.P.I. or 6 pitch			
	Number of feed changes	36			
	Longitudinal feed range	0.05~0.70 mm/rev			
	Cross feed range	0.025~0.35mm/rev			
	Inch threads	2~28 T.P.I. (36 kinds)			
	Metric threads	P0.8~14mm (65kinds)			
	D.P. No. / range	D.P 4-56 (36kinds)			
Module pitches No. / range	MOD 0.5~7 (22kinds)				
Tool slide	Cross slide travel	340mm	390mm	440mm	490mm
	Compound rest travel	240 mm			
Tailstock	Quill travel	180mm			
	Quill diameter	105mm			
	Taper of center	MT#6			
Motor	Main motor	15HP/4P, 20HP/4P (Opt.)			
	Rapid feed motor	1/4HP			
	Coolant pump	1/8HP			
Length (mm)	2700/3200/3700/4200/4700/5200/5700/6700/7700/8700/9700/10700/11700mm				
Width (mm)	1240				
Height (mm)	1400	1450	1500	1550	
N.W. (kg) (approx.)	3300/3600/3900/4200/4500/4800/5100/6100/7200/8300/9500/10700/11900kg				

Workpiece Weight capacity	Chuck only	Chuck + Tailstock	Chuck + 1 Steady rest + Tailstock	Chuck + 2 Steady rest + Tailstock
Spindle bore 105mm	600kg	1700kg	2700kg	4000kg
Spindle bore 155mm	1000kg	2000kg	3000kg	5000kg
Spindle bore 230mm	1400kg	2400kg	3400kg	5400kg

* ABOVE SPECIFICATIONS ARE FOR YOUR REFERENCE AND SUBJECT TO CHANGE WITHOUT NOTICE. FOR SPECIAL REQUIREMENTS PLEASE CONTACT US.

www.annnyang.com

OUR FACTORY

DY-410G~510G

DY-560G~760G

DY-680G~980G

DY-860G~1100G